

FF28LWHVAC



24.88" x 18.5" x 17.75" (H x W x D)

Compact medical all-refrigerator for temperature stable medical storage, with digital thermostat, lock, self-closing door, temperature alarm, and internal fan

Highlights:

Medical grade design conforms with CDC guidelines for vaccine storage

Specialized interior design protects stored contents when the door is open

Automatic defrost with an internal fan for stabilized cooling designed to stay within 2°C of set temperature

Product Features:

| | |
|-------------------------------------|--|
| Improved temperature stability | Interior is designed to operate within 2°C of set temperature performance |
| Interior drawer covers | Two shelves are protected by metal door flaps that help to protect stored contents from being exposed to room temperature when the door is opened |
| Digital thermostat | Electronic controls ensure precise and intuitive temperature management |
| High/low temperature alarm | Audible alarm sounds if the interior temperature rises or falls out of set range |
| NIST calibrated temperature display | Alarm includes NIST calibrated display of the current interior and high/low temperature |
| Self-closing door | Door closes automatically when opened at angles less than 90° to prevent the interior from being exposed to room temperature |
| Access port with contact | Pre-installed probe with contact allows users to install their own monitoring equipment; customers can specify placement of the access port upon order |
| Hospital grade cord and plug | Secure three-pronged 'green dot' cord for added unit safety in high traffic settings |
| Automatic defrost | Reduced maintenance with auto defrost system |

FF28LWHVAC Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 24.5" (62 cm) |
| Height to Hinge Cap | 24.88" (63 cm) |
| Width | 18.5" (47 cm) |
| Depth | 17.75" (45 cm) |
| Depth with door at 90° | 34.5" (88 cm) |
| Capacity | 0.8 cu.ft. (23 L) |
| Defrost Type | Automatic |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 1.3 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 60.0 lbs. (27 kg) |
| Shipping Weight | 63.0 lbs. (29 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101007175 |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R134a |
| Refrigerant Amount | 1.3oz. |
| High Side PSI | 261.0 |
| Low Side PSI | 103.0 |
| Level Legs Qty | 2 |
| Temperature Range | 2 to 8°C |
| Dimensions | |
| Interior Height | 11.38" (29 cm) |
| Interior Width | 14.0" (36 cm) |
| Interior Depth | 10.5" (27 cm) |

