accucold

ARS62MLMCBIADALK



31.75" x 23.38" x 25" (H x W x D)

Purpose-built MOMCUBE[™] all-refrigerator for breast milk storage disigned for freestanding or recessed installation, with 2 interior locking compartments, antimicrobial silverion handle, and hospital grade 'green dot' plug

Highlights:

Designed for use in NICUs, hospitals, maternity wards, lactation rooms, mothers' suites, and other facilities

Purpose-built for environments complying with Section 4207 of the Patient Protection and Affordable Care Act

Meets CDC guidelines with a temperature range of 33°F to 40°F

Product Features:

Purpose-built design	Designed and purpose-built for breast milk storage	
ADA compliant	Just under 32" tall designed to fit under ADA compliant counters	
Recessed or freestanding use	Versatile design allows recessed installation under counters or freestanding use	
Locking compartments	Two interior lockers sized at 11" H x 9 3/8" W x 15 $1/4$ " D accommodate standard and oversized nursing bottles and travel bags for individual privacy	
Combination locks	Allows each mother her own access system for added security	
Combination lock override	Locks can be reset or accessed by staff/managers as needed (2 keys included)	
Fully finished white cabinet	Allows the unit to be used freestanding	
Adjustable plastic-coated wire shelves for improved circulation	Shelves can be positioned with a front lip for small storage items or reversed to a flat position to better hold larger items, with multiple shelf positions spaced at 1/2" to accommodate virtually any size	
Microprocessor control panel	Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management	

ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@accucold.com



accuceld

ARS62MLMCBIADALK Specifications:

Overview	
Height of Cabinet	31.75" (81 cm)
Width	23.38" (59 cm)
Width with Door Open	23.88" (61 cm)
Depth	25.0" (64 cm)
Depth with Handle	26.75" (68 cm)
Depth with door at 90°	47.0" (119 cm)
Capacity	6.0 cu.ft. (170 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.75
Voltage/Frequency	115 V AC/60 Hz
Weight	135.0 lbs. (61 kg)
Shipping Weight	146.0 lbs. (66 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101078700
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Lockers
Shelf Qty	2
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	1.66oz.
High Side PSI	280.0
Low Side PSI	90.0
Low Side FSI	
Interior Light	Yes
	Yes 33°F to 40°F
Interior Light	
Interior Light Temperature Range	
Interior Light Temperature Range Dimensions	33°F to 40°F
Interior Light Temperature Range Dimensions Interior Height	33°F to 40°F 24.5" (62 cm)

6.5" (17 cm)
20.0" (51 cm)
5.0" (13 cm)



